

PERFORATED VINYL S/A ONE WAY VISION

OWMVXK1618040 UV PRINTING

Application

- Window Graphic
- Vehicle Graphic
- Signs & ADs

Technical Data Sheet

Item Code		OWMVXK1618040
PVC Face Film	Type	Monomeric PVC film
	Caliper (um)	160
	Open Rate	40%
Glue	Type	Clear removable solvent based acrylic glue
	Thickness (um)	25
	180° Peeling Force(N/in)	≥5.2N
	Holding Power	≥ 48Hours
Liner Paper	Type	SPE white paper
	Weight (gsm)	180
Available size	Width	0.914/1.06/1.27/1.37/1.52m (36"/42"/50"/54"/60")
	Length	50m/45.72m (164'/150')
Shelf Time (Month) (20°C x 50% R.H)		12 Months
Applying Temperature Range °C		-10~65°C
Outdoor durability		12 Months

Information contained in this document is based on our general experience and is given in good faith. But we are unable to accept responsibility in respect to factors which are outside our knowledge or control.

Ink Printability

SOLVENT	ECO-SOLVENT	UV	LATEX	SCREEN PRINTING
■	■	■		



Add: Room 912, No.3 Building, Shangdong Business Center, Haizhou District,
Haining, Zhejiang, China
Tel: +86-573-80776996 Fax: +86-573-80776998
Mob/Skype/Wechat/WhatsApp: +86-158-5832-2153
mailto:contact@hncomax.com

